

Product Information

BCSS015

Page 1/2

BestCure SS015

Dec. 2018 Version

Concrete curing compound, polysilicate based.

Description:	BestCure SS015 is polysilicate compounds for synthesis and maintenance of concrete during the curing process of cement.
Recommended for:	 Replace water for concrete maintenance after construction. For concrete in the harsh conditions and items construction. Use large block of concrete, well maintained, limited concrete surface cracks Use for tunnel concrete Use concrete for the floor should be concrete surface color.
Advantages:	 Improve the aesthetic value of the works. Easy maintenance. Non-toxic, can be used for domestic water tank. Improve the surface hardness of concrete maintenance. To prevent water evaporation effect on the concrete surface. Allow the next layer construction adhesive without surface treatment Reduce the maximum surface cracking phenomenon due to rapid dehydration. Suitable climatic conditions in Vietnam. Maintain a uniform color to surface hardener.
Technical data:	
Existence form:	Viscous liquid

Existence form:	Viscous liquid
Color:	Transparent
Component:	Polysilicate modified
Density:	1.20 ± 0.05 kg/liter.
pH:	10 ÷ 13
Package:	25 liter/ can; 210 liter/ drum.
Consumption:	8 ÷ 12 m ² /liter (depending on the surface condition)
Holding conditions:	Take a cool and dry place, ambient temperature: 5°C ÷ 35 °C
Shelf life:	12 months from the production date.

BESTMIX CORPORATION

HEAD OFFICE: Lot D1, D1&N3 Rd., Nam Tan Uyen IP, Tan Uyen Town, Binh Duong Province. Tel: (027) 4365 3990 - 4365 3991 Fax: (027) 4365 3992 Web:bestmix.vn Fax: (028) 3810 7998

HCMC OFFICE 2: 23 Nguyen Huu Canh Str. Ward 3 Binh Thanh Di BCSS015 Tel: (028) 3899 0339 - 3899 0340 Fax: (028) 3899 0340

DANANG OFFICE: 478B1 Dien Bien Phu Street, Thanh Khe District, Da Nang City. Tel: (023) 6371 5299 - 6371 5399 Fax: (023) 6371 5499

22

HANOI OFFICE: 02 Biet Thu 5 Str.,Linh Dam Pen., Hoang Liet, Tlaggea2/2anoi. Tel: (024) 3200 8234 - 3200 8235 Fax: (024) 3200 8235



Application

Surface preparation:	Concrete surfaces must be cleaned, not clogged with dust, dirt, mud, grease
Application:	Use roller or nozzle pressure to evenly distribute BestCure SS015 over the entire surface area of the concrete block after the concrete gets cured (hard surface).
Cleaning:	Clean material with water and proper soap immediately after used and before the material get hardens.
Safety:	BestCure SS015 could make an allergy to sensitive skin. Do not contact it for a long time. Should wear labor protection when application. Avoid contacting directly food, instruments of live activity, keep out of the reach of children. In case of accidental eye contact, wash with fresh water and seek medical advice immediately

Disclaimer:

The technical information and application instruction in documents of BESTMIX based on BESTMIX's current knowledge and practical experience. The information here only describes the general nature of product, so users should test the product for each purpose. BESTMIX has the right to change features of our product, user must always refer the latest technology product.

BESTMIX CORPORATION

HEAD OFFICE: Lot D1, D1&N3 Rd., Nam Tan Uyen IP, Tan Uyen Town, Binh Duong Province. Tel: (027) 4365 3990 - 4365 3991 Fax: (027) 4365 3992 Web:bestmix.vn Fax: (028) 3810 7998

HCMC OFFICE 1: 378-384 Cong Hoa Str., Ward 13, Tan Binh Dist., Ho Chi Minh City. Tel: (028) 3810 7995 (7996, 7997)

Tel: (028) 3899 0339 - 3899 0340 Fax: (028) 3899 0340

HCMC OFFICE 2: 23 Nguyen Huu Canh Str., Ward 22, Binh Thanh Dist., Ho Chi Minh City.

DANANG OFFICE: 478B1 Dien Bien Phu Street, Thanh Khe District, Da Nang City. Tel: (023) 6371 5299 - 6371 5399 Fax: (023) 6371 5499

HANOI OFFICE:

02 Biet Thu 5 Str.,Linh Dam Pen., Hoang Liet, Thanh Xuan, Hanoi. Tel: (024) 3200 8234 - 3200 8235 Fax: (024) 3200 8235