

## **BestRelease WB502**

Formwork Release compound, water-based.

Description:	BestRelease WB502 is a water-based organic compound, use to release the form of the shaping product or pouring concrete. To make shaping material and form do not stick together, and easily remove the mold.
Recommended for:	BestRelease WB502 is used as a form release agent for metal mold, plastics, wood, etc in the pouring concrete.  BestRelease WB502 is used as a form release agent for shaping fine art products, etc.
Advantages:	<ul> <li>Anti-stick form optimal.</li> <li>Improve the quality of the product surface after shaping.</li> <li>Protect the form is not damaged in the process of releasing the shaping material from the form.</li> <li>Does not contain corrosive material affect the shaping material as well as form.</li> <li>Low viscosity, easy to use.</li> <li>Non-toxic</li> <li>Don't contain an organic solvent, fire-safe.</li> </ul>
Testing:	The testing results are carried out according to the climatic conditions of Vietnam.
Technical data:	
Appearance:	Viscous liquid solution.
Color:	Milky white to light yellow
Density:	$0.89 \pm 0.03$ kg/liter.
рН	7.0 ÷8.0
The rate of dilution	: From 5 to 10 times
Storage conditions	: Keep in a cool and dry place.
<u> </u>	

## **BESTMIX CORPORATION**

Shelf life:

Package:

**Consumption:** 

www.bestmix.vn

5L; 25L/ can, 210L/ drum.

To wood form:

At least 12 months from manufacturing date (unopened condition).

To metal and plastic form: 20 – 30 m<sup>2</sup> /Liter.

10 - 15 m<sup>2</sup> / Liter.



The forming surface should be cleaned before applying.  Dirt and mud should be washed or cleaned.  Grease, oil, or old material should be cleaned with proper solvent when using BestRelease WB502 first.
Use a brush, roller, or spray nozzle to apply evenly BestRelease WB502 on the forming surface before applying the shaping product.  Do not apply surplus BestRelease WB502, to avoid BestRelease WB502 mixing into the shaping material, reducing the quality of the shaping material as well as waste materials.  Protect the newly applied BestRelease WB502 from rain. Once dry, BestRelease WB502 can be affected by the weather, not washed away when it rains.
Clean equipment and tools with a cloth immediately after application. Wear gloves, masks, and goggles when using the product. If the product contact with the eyes, nose, or mouth, should wash with clean water many times and go to the nearest medical facility for timely and correct treatment.
Keep in a cool, dry place. Close the lid tightly when not in use Do not leave the product in the wrong place.

## **Disclaimer**

The technical information and application instruction in documents of BESTMIX are based on BESTMIX's current knowledge and practical experience. The information here only describes the general nature of the product, so users should test the product for each purpose. BESTMIX has the right to change the features of our product, user must always refer to the latest technology product.

## **BESTMIX CORPORATION**

www.bestmix.vn